

/ Technical Information

A: Height 1500mm (58.5")

B: Width 150mm (5.8")

C: Depth 240mm (9.3")

Net Weight: 26.5Kg (59lb)


Cable Length: 2.5 + 2.5m (8.3 + 8.3ft)

DOUBLE CABLE


/ Supported Plugs




NACS



Type 1



Type 2



GB/T

Output:

Voltage Output: AC Single Phase 220V±10% / Three Phase 380±10%

Current Output: 32A/50A/64A/80A

Frequency: 50/60Hz

Technical Features:

Power Output: up to 44kW (cable A + cable B)

Cable Length: 2.5mt + 2.5mt / 8.20ft + 8.20ft

Working Temperature: -30°C+50°C / -22 / 122°F

Storage Temperature: -40°C+85°C / -29,2 / 185°F

Operating Humidity: ≤95%

Communication Interface: CAN with standard configuration, Ethernet, 4G

OCPP: 1.6/2.0.1

Enclosure Protection Grade: Indoor/Outdoor IP55

Communication Protocol: Qtech Background Protocol

Emergency Power Off Button: Yes

Protective Functionalities: Over-current Protection,

under-voltage/over-voltage protection, residual current,

lighting protection, short circuit protection,

over-temperature protection, grounding fault protection

Installation Type: Floor fixation system

Charging method: Plug and Charge/Scan code to Start

/ Customizable internal components on request

The Stylo Up for two

